

DT 200

Shurtape®
TRUE TO YOUR WORK™

PREMIUM PERFORMANCE GRADE DOUBLE-COATED NONWOVEN TISSUE TAPE

TYPICAL APPLICATIONS

- For high-speed splicing in the corrugated cardboard production process in temperatures up to 400 F
- Can also be used as a mounting and laminating system for irregularly shaped metals, foams, foils and nameplates
- For manual applications

PRODUCT FEATURES

- High adhesion and quick stick
- Superior temperature resistance up to 400 F
- Excellent conformability to irregular surfaces
- Hand-tearable

CONSTRUCTION

Overall Grade/Function: Premium Performance
Backing: Nonwoven tissue
Adhesive: Solvent-based acrylic
Liner: Glassine

STANDARD WIDTH(S)

12 mm 18 mm 24 mm 36 mm 48 mm 72 mm

STANDARD LENGTH(S)


50 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

| | STANDARD | METRIC |
|-----------------------------|------------------|----------------|
| Tensile Strength | 4.6 lbs/in width | 8.0 N/10 mm |
| Adhesion to Stainless Steel | 55 oz/in width | 6.02 N/10 mm |
| Thickness (with liner) | 7 mils | 0.18 mm |
| Thickness (without liner) | 4.5 mils | 0.11 mm |
| Elongation | 3.5% | 3.5% |
| Service Temperature Range | -20 F to 212 F | -29 C to 100 C |

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

